THE CLAIMS

Please amend the claims as follows:

1. (Withdrawn) An implantable unit comprising: an input circuit to provide a sampled signal;

a controller coupled to the input circuit wherein the controller receives the sampled signal and generates a plurality of characteristic points as a function of a curvature series based on the sampled signal, wherein each characteristic point includes a time component corresponding to a time of occurrence of a lobe of the curvature series and wherein each characteristic point includes an amplitude component of the sampled signal at the time of occurrence; and

a memory coupled to the controller and adapted to store each characteristic point of the plurality of characteristic points.

- 2. (Withdrawn) The unit of claim 1 wherein the controller is adapted to generate, for each characteristic point, a size component as a function of an area of the lobe of the curvature series.
- 3. (Withdrawn) The unit of claim 2 wherein the controller is adapted to discard without storing in the memory, a characteristic point associated with a size less than a predetermined value.
- 4. (Withdrawn) The unit of claim 1 wherein the controller is adapted to generate a first data set corresponding to a first group of characteristic points and the memory is adapted to store the first data set.
- 5. (Withdrawn) The unit of claim 4 wherein the controller is adapted to store a repetition marker corresponding to a second data set wherein the second data set includes a second group of characteristic points that substantially match the first group of characteristic points and wherein the repetition marker identifies the first data set.

Page 4

Dkt: 279.635US1

(Withdrawn) The unit of claim 5 wherein the controller is adapted to store a time value 6. associated with the repetition marker, the time value determined as a function of a time of

occurrence of the second data set.

(Withdrawn) The unit of claim 4 wherein the controller is adapted to store a difference 7.

marker corresponding to a second data set wherein the second data set includes a second group

of characteristic points that differs from the first group of characteristic points and wherein the

difference marker identifies the first data set.

(Withdrawn) The unit of claim 7 wherein the controller is adapted to store difference 8.

data associated with the difference marker, the difference data corresponding to a difference

between the first data set and the second data set.

(Withdrawn) The unit of claim 1 wherein the controller includes a processor and wherein 9.

the memory includes executable instructions accessible to the processor.

(Withdrawn) The unit of claim 1 wherein the controller includes hardwired circuitry. 10.

(Withdrawn) The unit of claim 1 wherein the controller includes a filter adapted to 11.

generate a running average of the sampled signal.

(Withdrawn) The unit of claim 1 wherein the controller includes a comparator. 12.

(Withdrawn) The unit of claim 1 wherein the time of occurrence of the lobe includes a 13.

time of occurrence of a centroid of the lobe.

receiving a sample series corresponding to a signal sampled at a predetermined rate; for each sample in the sample series, calculating a curvature to form a curvature series using a processor, the curvature series corresponding to a curvature signal;

identifying a lobe in the curvature series, the lobe corresponding to a portion of the curvature signal starting when the curvature signal crosses a first threshold in one direction and ending when the curvature signal crosses a second threshold in an opposite direction;

calculating an area of the lobe between the portion of the curvature signal corresponding to the lobe and a baseline; and

for an <u>if the</u> area <u>is</u> greater than a predetermined value, identifying a parameter for the lobe and storing a characteristic point in a memory, the characteristic point including a time of the parameter and an amplitude corresponding to the time of the parameter.

- 15. (Original) The method of claim 14 wherein identifying the parameter includes identifying a centroid.
- 16. (Original) The method of claim 14 wherein receiving a sample series corresponding to the signal sampled at the predetermined rate includes receiving a sample series generated as a function of an electrocardiogram sampled at a predetermined rate.
- 17. (Original) The method of claim 14 wherein the signal is a function of a sensor signal.
- 18. (Original) The method of claim 14 wherein the signal is a function of time.
- 19. (Original) The method of claim 14 wherein the signal is a function of temperature.
- 20. (Original) The method of claim 14 wherein the signal is a function of an impedance.
- 21. (Original) The method of claim 14 further including receiving the predetermined value.

as a function of changes in the sampled signal.

23. (Currently Amended) The method of claim 14 wherein identifying the lobe includes

identifying a first time when an absolute value of the amplitude of the curvature series is greater

than [[a]] the first threshold and identifying a second time when the absolute value of the

amplitude of the curvature series is less than [[a]] the second threshold.

24. (Original) The method of claim 23 wherein the second threshold is less than the first

threshold.

25. (Currently Amended) The method of claim 14 further including, for an if the area is

greater than the predetermined value, storing a code as a function of the predetermined rate.

26. (Original) The method of claim 14 wherein storing the characteristic point is performed

in real time relative to receiving the sample series.

27. (Original) The method of claim 14 wherein receiving the sample series includes

accessing stored sample data.

28. (Original) The method of claim 14 further including storing a repetition marker to

indicate that a later plurality of characteristic points substantially matches an earlier plurality of

characteristic points.

29. (Original) The method of claim 28 wherein storing the repetition marker includes storing

identification data that identifies the earlier plurality of characteristic points.

30. (Original) The method of claim 28 wherein storing the repetition marker includes storing

temporal data that identifies a time of occurrence of the later plurality of characteristic points.

Title: SIGNAL COMPRESSION BASED ON CURVATURE PARAMETERS

- 31. (Original) The method of claim 28 wherein storing the repetition marker includes storing a code to indicate a number of consecutive repetitions of the earlier plurality of characteristic points and a time interval between consecutive repetitions.
- 32. (Original) The method of claim 14 further including storing a difference marker to indicate that a later plurality of characteristic points differs from an earlier plurality of characteristic points.
- 33. (Original) The method of claim 32 wherein storing the difference marker includes storing identification data that identifies the earlier plurality of characteristic points.
- 34. (Original) The method of claim 32 wherein storing the difference marker includes storing temporal data that identifies a time of occurrence of the later plurality of characteristic points.
- 35. (Original) The method of claim 32 wherein storing the difference marker includes storing difference data generated as a function of a comparison of the earlier plurality of characteristic points and the later plurality of characteristic points.
- 36. (Original) The method of claim 14 further including, for each characteristic point, storing a start time value determined as a function of a start time for the lobe in the curvature series.
- 37. (Original) The method of claim 14 further including, for each characteristic point, storing an end time value determined as a function of an end time for the lobe in the curvature series.
- 38. (Original) The method of claim 14 further including reconstructing the sampled series by connecting adjacent characteristic points with line segments.

Title: SIGNAL COMPRESSION BASED ON CURVATURE PARAMETERS

- (Original) The method of claim 14 further including reconstructing the sampled series by 39. connecting adjacent characteristic points with a polynomial equation.
- (Original) The method of claim 14 further including reconstructing the sampled series by 40. connecting adjacent characteristic points with a cubic spline equation.
- (Original) The method of claim 14 further including reconstructing the sampled series as 41. a function of the area of each lobe in the curvature series.
- (Original) The method of claim 14 further including reconstructing the sampled series as 42. a function of a start time of each lobe in the curvature series.
- (Original) The method of claim 14 further including reconstructing the sampled series as 43. a function of an end time of each lobe in the curvature series.
- (Original) The method of claim 14 wherein the sampled signal includes an 44. electrocardiogram and further including:

identifying a plurality of characteristic points; and delivering therapy as a function of the plurality of characteristic points.

(Withdrawn) A system comprising: 45.

an input circuit adapted to receive a sampled signal;

a curvature series generator coupled to the input circuit and adapted to generate a curvature series as a function of the sampled signal; and

a memory coupled to the curvature series generator and adapted to store a plurality of characteristic points, each characteristic point having time data and amplitude data derived from the curvature series.

(Withdrawn) The system of claim 45 wherein the input circuit is coupled to a cardiac 46. electrode.

Page 9 Dkt: 279.635US1

- 47. (Withdrawn) The system of claim 45 wherein the curvature series generator includes a circuit adapted to identify a centroid of a lobe in the curvature series.
- 48. (Withdrawn) The system of claim 45 wherein the curvature series generator includes a circuit adapted to identify a start time of a lobe in the curvature series.
- 49. (Withdrawn) The system of claim 45 wherein the curvature series generator includes a circuit adapted to identify an end time of a lobe in the curvature series.
- 50. (Withdrawn) The system of claim 45 wherein the curvature series generator includes a processor.
- 51. (Withdrawn) The system of claim 45 wherein the curvature series generator includes a processor adapted to generate an area of a lobe in the curvature series.
- 52. (Withdrawn) The system of claim 45 further including a telemetry circuit to wirelessly communicate the plurality of characteristic points stored in the memory.
- 53. (Withdrawn) An implantable medical device comprising:

 means for receiving a data series corresponding to a sampled signal;

 means for generating a curvature series as a function of the data series;

 means for identifying a plurality of characteristic points as a function of the curvature series, each characteristic point having a time component and an amplitude component; and means for storing selected characteristic points of the plurality of characteristic points.
- 54. (Withdrawn) The implantable medical device of claim 53 wherein the means for identifying includes means for determining a size of a characteristic point as a function of an area of a lobe in the curvature series.

- 55. (Withdrawn) The implantable medical device of claim 54 further including means for selecting a characteristic point having a size greater than a predetermined value.
- 56. (Withdrawn) The implantable medical device of claim 53 wherein the sampled series includes an electrocardiogram and further including means for selecting a first group of characteristic points from the plurality of characteristic points, wherein the first group of characteristic points is associated with a first morphological feature of the electrocardiogram.
- 57. (Withdrawn) The implantable medical device of claim 56 wherein the means for storing selected characteristic points includes means for storing feature data corresponding to the first group of characteristic points.
- 58. (Withdrawn) The implantable medical device of claim 56 wherein the means for storing feature data includes:

means for storing a repetition marker corresponding to a repetition of the first group of characteristic points;

means for storing identification data for the first group of characteristic points; and means for storing temporal data as a function of a time of occurrence of a second group of characteristic points, wherein the second group of characteristic points is substantially similar to the first group of characteristic points.

59. (Withdrawn) The implantable medical device of claim 56 wherein the means for storing feature data includes:

means for storing a difference marker corresponding to a difference between the first group of characteristic points and a second group of characteristic points, wherein the second group of characteristic points is associated with a second morphological feature that occurs subsequent to the first morphological feature;

means for storing identification data for the first group of characteristic points; and means for storing temporal data as a function of a time of occurrence of the second group of characteristic points.

Title: SIGNAL COMPRESSION BASED ON CURVATURE PARAMETERS

60. (Withdrawn) An article comprising a machine-accessible medium having associated data

wherein the data, when accessed, results in a machine performing:

receiving a data series corresponding to a sampled signal;

generating a plurality of characteristic points based on a curvature series of the data

series, each characteristic point generated as a function of a time of occurrence of a lobe in a

portion of the curvature series and an amplitude at the time; and

storing the plurality of characteristic points.

61. (Withdrawn) The article of claim 60 wherein the data, when accessed, further results in

the machine generating each characteristic point as a function of an area of the lobe in the

curvature series.

62. (Withdrawn) The article of claim 60 wherein storing the plurality of characteristic points

includes storing those characteristic points having an area greater than a predetermined value and

deleting those characteristic points having an area less than the predetermined value.

63. (New) The method of claim 14 wherein identifying the parameter for the lobe includes

determining a size of the characteristic point as a function of the area of the lobe.